

FOX IV 5400 Series Zebra® Based Printer-Applicators

**FOX IV Technologies 5400 series**

featuring Zebra print engines are rugged, dependable label printer-applicators with the versatility to meet most labeling applications.

Compatibility: Have an existing Zebra desktop printer? The FOX IV 5400 series Printer-applicators are compatible with the ZPL® programming language and ZebraNet™ Print Server enabling use of existing data streams.

Ease of Use: Designed to be simple to operate and maintain, the 5400 series has many user-friendly features. Media changes are fast and simple with silk screened media paths and a standard Swing-Away cylinder which allows full access to the print engine for media loading and print head changes. The

rotatable control panel ensures that operators can easily check settings and indicators.

Production Ready: With 4 different print engines and two printer-applicator sizes, the 5400 series can fit into most existing production lines. The compact Mini is ideal for low-run or space limited environments while the workhorse Standard enables extended production runs.

Customizable: Customize the 5400 to meet your specific application needs from two-panel labeling, wrap-around, delicate surfaces and more. Our in-house engineering team can design solutions to meet the most challenging labeling applications.

FEATURES

- Mini and Standard Sizes for production efficiency
- 4 print engine sizes
- Compatible with Zebra desktop printers, ZebraNet
- Rotatable, multilingual backlit LCD control panel for ease of use
- Swing-away cylinder for access to print head
- Industrial design
- Screened media paths to ensure accurate label and ribbon loading
- Standard and custom application apparatus

TECHNICAL SPECIFICATIONS - 5400 Series Zebra Printer-Applicators

MODELS: 5410 Mini Label Printer-Applicator
 5410 Standard Label Printer-Applicator
 5440 Standard Label Printer-Applicator
 5470 Standard Label Printer-Applicator
 5422 Standard Label Printer-Applicator



Printer Details	5410 Mini	5410 Std.	5440	5470	5422
Method	Thermal Transfer or Direct Thermal				
Resolution	203, 300, 600 dpi		203 or 300 dpi		
Max. Print Speed	10/8/4 ips (254/203/102 mmps)		10 ips (254 mmps)		
Max. Print Length	39" (991 mm)				
Label Liner Min.	.79" (20 mm)		1.57" (40 mm)	2" (51 mm)	4.25" (108 mm)
Label Liner Max.	4.5" (114 mm)		5.51" (150 mm)	7.1" (180 mm)	8.8" (223.5 mm)
Size	18"H X 13.6"D x 18"W (457 x 345 x 457 mm)	18"H x 13.6" D x 26" W (457 x 345 x 660 mm)	18"H x 14.4" D x 26" W (457 x 365 x 660 mm)	18"H x 16.4" D x 26" W (457 x 417 x 660 mm)	18"H x 18.5"D x 26" W (457 x 470 x 660 mm)
Weight	56 lbs (25.4 kg)	101 lbs (45 kg)	105 lbs (48 kg)	109 lbs (49.4 kg)	115 lbs (52 kg)
Label Roll Size					
Max. Roll OD	10" (254 mm)	16" (406 mm)			
ID/Core Sizes	3" (76 mm)	3", 5" or 6" (76, 127, 152 mm)			
Operating Environment					
Power Supply	Universal w/power-factor correction 90V-264V AC, 48-62 Hz				
Air	80-100 psi				
Temperature	40° - 104° F (5° - 40° C)				
Relative Humidity	Max. 95% non-condensing				
Applicator Options					
Swing-Away Cylinder (standard), rotary actuator, Repeater™ two-panel, Sidewinder™ wrap-around, tamp, tamp-blow, blow-on, gimbal pad, custom application methods					
Interfacing Capabilities					
<ul style="list-style-type: none"> Flash Memory (4 MB, 2MB available to user) and SDRAM (16 MB, 12 MB available) High-speed bi-directional IEEE 1284 parallel interface • USB 2.0 Port (480 MBps) High-speed serial interfaces: RS232C/422/485 multi-drop (optional adapter) ZebraNet™ Wireless 10/1000 and PrintServerII Print Servers • IBM Twinax, Coax 					
Bar Code Symbologies					
All major linear and 2D symbologies including QR, Datamatrix, Aztec, & MicroPDF					
Options & Accessories					
<ul style="list-style-type: none"> Compact Flash Cards • XML Enabled Printing • 64 MB On-board Linear Flash Memory Firmware support for downloadable TrueType™; additional fonts available • RFID 					

Shipping Containers

Electronics

Pallets

Books

Totes

Soft Packaging

Food & Beverage

Specifications subject to change without notice.



FOX IV TECHNOLOGIES, INC.

6011 ENTERPRISE DRIVE, EXPORT, PA 15632 | PHONE: 1.724.387.3500 | FAX: 1.724.387.3516

VISIT US ONLINE AT WWW.FOXIV.COM



Leading companies. Leading solutions.